

## Product Details

The Kytun Tile Dry Verge System permanently secures tiles on gable ends and gives an attractive maintenance free finish to the roofline. The design helps protect the edge of roof tiles from the elements and eliminates the possibility of lifting and damage to the roof underlay. No mortar or timber guides are required. It can be bespoke manufactured to virtually any profile to suit individual requirements.

## Product Features

- Provides full wind uplift and rain protection.
- Extremely easy and quick to install.
- Requires no maintenance once installed.
- Can be fully customised.
- Available in a range of colours: Black, Blue/Black, Brown & White.
- Powder coated colours also available on request.

## Dimensions

### C08ES/C08E Aluminium

Overall length: 2400mm & 3000mm

| Code  | Size           | Colour                      | Pk Qty |
|-------|----------------|-----------------------------|--------|
| C08ES | 50mm x 2.4m/3m | Blk • Blue/Blk • Brwn • Wht | 4      |
| C08E  | 65mm x 3m      | Blk • Blue/Blk • Brwn • Wht | 4      |

Fully compatible with most tiles on the market.  
Suitable for brick, render & bargeboard construction.

50mm Version: Suitable for a maximum individual tile thickness of 25mm.

65mm Version: Suitable for a maximum individual tile thickness of 32mm.

### BESPOKE VERSIONS AVAILABLE

The C08E range can be bespoke manufactured to accommodate all sizes and virtually any profile to suit individual requirements.

## Compatibility

Fully compatible with most tiles on the market. Suitable for brick, render and bargeboard construction.

