

## Slate Roof Terminal

SDA101/SDA102

### Installs in a flash on Slate Roofs

Slate Roof Terminal won't stain or corrode roofs and gutters. The EPDM cone, which is trimmed on site to fit, is ingeniously locked to a high grade and malleable 99.9% pure aluminium base. The fast economical way to flash a tile roof.

Pipe External	Roof Pitch	Base Size	Base Type	Code Black EPDM
50 - 170mm	0-45°	500 x 600mm	Aluminium	SDA101
110 - 200mm	0-45°	600 x 600mm	Aluminium	SDA102



## Tile Roof Terminal

SNL101/SNL103

### No more concern about Unprotected Lead

The Tile Roof Terminal has been developed for use where the handling of lead and associated environmental issues are of concern. Combines a long-life, weather-resistant EPDM cone with a grey primed acrylic coated lead base. The unique thermo-baked coating does not affect the lead's malleability, and prevents leaching onto the roof and into gutters, downpipes and the water table.

Pipe External	Roof Pitch	Base Size	Base Type	Code Black EPDM
50 - 170mm	0-45°	600 x 450mm	Nu-Lead	SNL101
175 - 330mm	0-45°	850 x 550mm	Nu-Lead	SNL103



CAN BE USED WITH:

INSULATED CHIMNEYS • SOIL PIPES • VENTILATION PIPES